

 **First in Quality. Built to Last.**



BB-2

BOTTOM BELT CASE TAPER

EASTEY DELIVERS WHAT YOU NEED. . . TODAY

Easteys's BB-2 case taper is a cost-effective top and bottom case taper designed for large run case sealing. BB-2 features self-centering side rails, a rugged bottom belt drive, and heavy-duty mast that easily adjusts to handle a variety of case sizes.

INNOVATIVE TECHNOLOGY, PROVEN RELIABILITY

BB-2 offers the durability, versatility and reliability that you have come to rely on from Easteys. The system's unique and simple design has proven to be one of the most reliable case tapers on the market today, keeping production and maintenance efforts to a minimum and providing fast and efficient alternatives to hand taping.

TRUE VERSATILITY FOR YOUR NEEDS

BB-2 offers fast and easy case changes with adjustable side rails and flexibility ranging from 5" to infinite box length. BB-2 is also able to seal cases ranging from 6" to 21" in width, as well as 4" to 20.5" in depth. Adjustments can be made on the fly with easy hand tighten knobs on a single mast design. BB-2's open design is also perfect for integration with ink jet printers where coding is required on boxes.


EASTEY
First in Quality. Built to Last.

COST-EFFECTIVE CASE SEALING

BB-2 features self-centering side rails, a rugged bottom belt drive, and heavy-duty mast that easily adjusts to handle a variety of case sizes at a cost-effective price.

CASE TAPING AS EASY AS 1-2-3

BB-2 top and bottom tape heads are interchangeable and tip back for easy threading. No air is required to run the BB-2 taping system so it can be placed anywhere in the factory. A safe single mast allows clear access to all components and adjusts for a variety of case sizes. The use of Easteys's BB-2 case taping machine can be learned in minutes, avoiding breaks in production and downtime, saving your company money and increasing your ROI.





INDUSTRIAL STRENGTH OPERATION

A single drive motor and aggressive industrial strength drive belts make BB-2 a workhorse that will stand up to your toughest challenges. Each case taping machine is made from 12 gauge steel that withstands even the most rugged applications. A powder coated exterior protects the machine from abusive conditions and guarantees years of use.

THE RIGHT SOLUTION

Rugged design. Proven reliability. Simple operation. Your benefits go on and on. When it comes to industrial operation, rely on Easteys to provide the right solution for your case sealing needs.

BB-2 BOTTOM BELT CASE TAPER



1. Top and bottom tape heads are interchangeable and tip back for easy threading
2. Industrial strength drive belts move boxes consistently through the taper
3. Adjustable side rails and tape head offer fast and easy case changes
4. Top and bottom tapeheads are identical and can be removed instantly without tools. Choose from two options.

BB-2 FEATURES	BB-2 TAPING SPECIFICATIONS			
<ul style="list-style-type: none"> • Plug-in and go operation • Powder coated 12 gauge steel • Interchangeable top and bottom tape cartridges • Adjustable side rails • Industrial strength drive belts • Safe single mast design • Easy hand-tighten adjustments • No air required • Low maintenance • Simple integration with ink jet printers • Includes 2 pack tables and casters 	Sealer Type	Bottom belt, top and bottom case sealer		
	Machinery Makeup	Industrial strength 12 gauge steel, powdered coated for durability		
	Belt Speed	60 feet/per minute		
	Tape Speed	30 cases/per minute, depending on box size and operator efficiency		
	Casters	Rugged wheels for transportation within plant		
	Front and Rear Packing	Solid tables bolt before and/or after taping system to allow for case packing		
	Adjustable Side Rails	Palm grip knobs offer quick and simple adjustments		
	Height Adjustment	Standard adjustable legs for 22.25" to 35.25" conveyor heights		
	BOX SPECIFICATIONS	Length	Width	Depth
	Minimum Box Size	5"	6"	4"
Maximum Box Size	Infinite	21"	20.5"	
Tape Size	2" wide pressure sensitive tape, up to 15" diameter rolls, optional 3" wide tape			
Tape Cartridge	Proven design requires no lubrication, tips back for simple tape threading, removable for maintenance and interchangeable with top or bottom cartridges			
Air Requirements	None			
Electrical Requirements	110 VAC, 60Hz, 6A			

BB-2 OPTIONAL ACCESSORIES	
3" Tape Head	Accepts 3" wide tape rolls
Top Squeezers	Designed to stabilize the box and push the top flaps together for easier taping



7041 Boone Avenue North, Brooklyn Park, MN 55428
 (763) 428-4846 1 (800) 835-9344
 www.eastey.com info@eastey.com

