

# Clamco Heavy Duty L-Bar Sealers


## High-Performance L-bar Sealers

The Clamco heavy duty L-bar sealers are available in several sizes—4L, 6L, and the extra large 8L for packaging and sealing a variety of products. Clamco heavy duty L-bar sealers can be used with a wide range of films due to their precise temperature and speed controls. These dependable L-bar sealers are equipped with a sealing arm that works manually, pneumatically, or with a motor (motorized closing on the 6L and 8L). The robust design of the Clamco systems provides the framework for greater productivity and ensures consistently strong seals.


The use of integrated application-specific controls allow for easy and fast operator set-up and provide years of trouble-free operation. The Clamco L-bar sealers offer a hot knife seal bar option for sealing PVC and polyethylene films. In addition to the temperature control, the Clamco L-Bar sealer has dwell control for continued seal time under pressure, and speed control for the product power take-away conveyor. The Clamco system also has a convenient adjustable height control for the power take-away conveyor to provide smooth product transfer.

The Clamco heavy duty L-bar sealers are 24/7 machines that minimize maintenance, provide consistently strong seals and can be used with a wide range of films.

The Clamco heavy duty L-bar sealer is made in the USA and includes a 3 year limited warranty.



*Film tracking roller and film separator for easy packaging loading*



*Temperature controlled impulse seal wire*



*Tubular 1.5" diameter heavy duty seal bar*

### Operating Features

- Power take-away conveyor for automatically transporting the product from the seal area
- Automatic closing seal bar arm (optional)
- Heavy duty frame construction provides 24/7 operation
- Easy-to-use operator controls enhance operator effectiveness
- Independent dwell control allows flexibility for utilizing a wide range of films

### Set-up Features

- Cycle delay sets the time between cycles in automatic mode (optional)
- Lower Film Cradle gives the machine a smaller footprint

### Sealing Features

- Large dual magnetic hold down ensures consistent seal pressure
- Height adjustable, heavy duty seal head with stainless steel film clamps
- Unique temperature control provides consistent seals and longer wire life
- Spring tension adjustment enhances seal arm counterbalance and return speed
- Pin perforation wheels allow for ventilation and excellent shrink

### Safety Features

- Cycle start button for operator safety
- Locking casters for safety and stability
- CE compliant design for enhanced troubleshooting



a PAC Machinery company

## L-bar Sealer Options

- Automatic closing seal arm increases production rate
  - motor operated (6L and 8L only)
  - pneumatically operated (4L and 6L)

Hot Knife with mushroom blades for sealing PVC and Polyethylene films

PTFE Coated Seal Wire for use with PVC and Polyethylene films

## Operating Options

Double Film Cradle for twice the capacity of machine film

## Operating Options (cont'd)

Film Inverting Head with power film unwind ensures high-speed productivity

Power Film Unwind electrically moves film roll to ensure film consistency

Trim Take-Up Wheel to automatically rewind trim

Blower Table adds air to the film for easier product loading

316 Stainless steel construction for damp environments

Package Lift for assistance with heavy or oversized products (8L only)

Foot Switch Cycle Activation—Instead of using the start button, the cycle is activated via a foot switch. With this option, the operator can have both hands free to load the product. (requires automatic closing option)

## Specifications

Model	Clamco 4L	Clamco 6L	Clamco 8L
Seal length (end)	19"	27.5"	39"
Seal length (side)	22"	33"	50"/69"/88"
Maximum film width	24"	32"	52"
Overall Dimensions	35"L x 27.5"W x 36"H	60"L x 36"W x 36"H	87"/101"/119"L x 51"W x 41"H
Electrical	220 Volt, 10 amp, 1 Ph	220 Volt, 10 amp, 1 Ph	220 Volt, 20 amp, 1 Ph
Shipping Weight	450 lbs	600 lbs	1300 lbs



## Contact us today:

1 (234) 222-1000 ■ [sales@pacmachinery.com](mailto:sales@pacmachinery.com)



a PAC Machinery company

775 Berea Industrial Parkway, Berea OH 44017 ■ 1 (234) 222-1000 ■ [pacmachinery.com](http://pacmachinery.com)

Specifications subject to change without notice