HEAVY DUTY VERTICAL BAND SEALER MODEL VBS-3/8-DH-10

FOR DIFFICULT TO SEAL POUCH / BAG MATERIALS

- USDA Approved Vertical Rotary Band Sealing System.
- Easy Interfacing Use your existing conveying equipment by positioning the sealing system over it and adjusting the sealer's variable speed drive to match.
- Extra sealing capacity allows speeds up to 720" per minute (60 fpm) with constant secure seals of 1/4" or 3/8" wide. Actual sealing speed depends on structure and thickness of material being sealed.
- Designed to seal virtually all sealable films, including Kraft/PE, Nylon, Polyethylene, Polypropylene, Laminates, Tyvek / Polymylar and Foil.
- Quality seals are achieved through the use of special heavy duty wear-resistant laminated Teflon bands.



- Unit is designed with two 5" heating sections (10" total) and two 5" cooling sections (10" total) for greater flexibility in product sealing of difficult materials with temperatures up to 500 degrees +/- 2 degrees Fahrenheit.
- Dual temperature controls with PID Autotune maintain consistent heat and assures quality hermetic seals.
 Individual heating assemblies can be regulated because of dual controls.
- Front Heater On/Off switch for Tyvek pouches is a standard feature.



- Mounted on a heavy duty floor model adjustable height stand with crank handle. Standard vertical model can be modified to operate in a horizontal position as an option. Unit can be positioned over existing lower carry conveyor.
- Hard Chrome plated sealing bars followed by Nickel plated cooling bars allow for maximum wear resistance.
- No compressed air required, 110V, 1 Phase, 60 Cycle.
- Optional Date Coder for product marking is available upon request.

APPLICATIONS

| Medical | Chemicals | Food |
|----------------|----------------|--------|
| Pharmaceutical | Meat & Poultry | Bakery |
| Textiles | Mailroom | Pet |
| Decorative | Automotive | Crafts |
| Seafood | House wares | Garden |



OVER 50 YEARS OF SUCCESSFUL PACKAGING EXPERIENCE

ALL PACKAGING MACHINERY, CORP.